

# 3D print water jet cleaning station

## PolyJet Waterjet



**Tool Type:** Post-processing

**Location:** Microfluidics Lab

**Description:** Presssure washer

**Manufacturer:** Stratasy

Last updated 1/5/23 Haley

---

## About

This tool removes support material from parts 3D printed by the Objet 30.

---

## Safety Concerns

- Lid should remain latched and closed whenever the machine is on
- Water should be shut off to the machine imminently after cleaning is finished to avoid accidental flooding
- Cracked protective gloves should imminently be replaced
- Do not operate water jet outside of sealed container

## Operating Procedures

1. First remove the bulk of the Objet support material (FullCure705) with the cleaning implements found next to the pressure washer. Wear gloves as uncured resin may be on the surface of the part.
  2. Place part within the pressure washer and open the DI valve on the sink. The power switch is located on the back of the washing enclosure.
  3. Using the foot pedal, clean the part using the high pressure nozzles located within the enclosure
  4. After part has been cleaned, **ensure the water is switched off** as leaks have occurred within Elings Hall before and will damage equipment
  5. To achieve optimal mechanical properties, or if part is to be used as a mold for casting, part should be baked at 60 degrees C for a minimum of 4 hours
- 

## Detailed Specifications

- Water consumption: less than 12 L/min
  - 85-88 dB when operating
- 

## Reference Documentation

[Objet 30 Users Outline and SOP](#)

[objet\\_waterjet\\_installation\\_and\\_user\\_guide\\_-\\_english.pdf](#)

---

From: <https://microfluidics.cnsi.ucsb.edu/wiki/> - Innovation Workshop Wiki

Permanent link: [https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=3d\\_print\\_water\\_jet\\_cleaning\\_station&rev=1672965302](https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=3d_print_water_jet_cleaning_station&rev=1672965302)

Last update: 2023/01/06 00:35

