

Bambu Lab H2D 3D Printer

H2D	
	
Tool Type: 3D printer	
Location: uFL 3430	
Description: FDM 3D printer	
Manufacturer: Bambu Lab	

About

The Bambu Lab H2D is located in Elings 3430 besides the X1Cs. It is an FDM printer which extrudes melted filament onto a textured build plate. Currently, it uses ABS, PLA, PETG, and TPU; all in a very limited variety of colors. It's one of our fastest printers while still maintaining a high quality.

Detailed Specifications

Nozzle tip sizes: 0.2 mm nozzle, 0.4 mm nozzle, 0.6 mm nozzle
Single Nozzle Build volume: 325 mm x 320 mm x 325mm
Dual Nozzle Build volume: 300 mm x 320 mm x 325mm
X,Y accuracy: ~200 microns Max Nozzle Temp: 350 C Max Heatbed Temp: 120 C Max Chamber Temp: 65 C

Training Documents

[H2D SOP](#)

Reference Documentation

[Product Overview](#)

[Product Specs](#)

From:

<https://microfluidics.cnsi.ucsb.edu/wiki/> - **Innovation Workshop Wiki**

Permanent link:

<https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=bambulabh2d>

Last update: **2025/09/25 21:14**

