

# Bambu Lab H2D 3D Printer

<b>H2D</b>
<a href="#">h2dphoto.png_400</a>
<b>Tool Type:</b> 3D printer
<b>Location:</b> uFL 3430
<b>Description:</b> FDM 3D printer
<b>Manufacturer:</b> Bambu Lab

---

## About

The Bambu Lab H2D is located in Elings 3430 besides the X1Cs. It is an FDM printer which extrudes melted filament onto a textured build plate. Currently, it uses ABS, PLA, PETG, and TPU; all in a very limited variety of colors. It's one of our fastest printers while still maintaining a high quality.

---

## Detailed Specifications

Nozzle tip sizes: 0.2 mm nozzle, 0.4 mm nozzle, 0.6 mm nozzle

Single Nozzle Build volume: 325 mm x 320 mm x 325mm

Dual Nozzle Build volume: 300 mm x 320 mm x 325mm

X,Y accuracy: ~200 microns Max Nozzle Temp: 350 C Max Heatbed Temp: 120 C Max Chamber Temp: 65 C

---

## Training Documents

[H2D Training](#)

---

## Reference Documentation

[H2D SOP](#)

[Product Overview](#)

[Product Specs](#)

From:

<https://microfluidics.cnsi.ucsb.edu/wiki/> - **Innovation Workshop Wiki**

Permanent link:

<https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=bambulabh2d&rev=1759941374>

Last update: **2025/10/08 16:36**

