Electro-Technic BD-20AC Corona Treater

Electro-Technic Corona Treater



Tool Type: Surface treatment **Location:** Microfluidics Lab

Description: High frequency generator used for surface treating of polymers

Manufacturer: Electro-Technic Products Inc.

About

Corona discharge wands use a high frequency electric field to ionize the surrounding air over a very short range. In principle, their operation is similar to a tesla coil, which accumulates charge until a high enough voltage is reached to produce a spark. In this case, the spark rate is around 100-120 Hz, double the line frequency. Each spark produces a small amount of plasma (as indicated by the light produced) which creates active ions that increase the surface energy of polymers.

Safety Concerns

High Voltage - Keep the electrode tip away from your body. Care should be taken to prevent the electrode from arcing to any worn metal items, such as jewelry. Since this is a very low current device, a spark will cause discomfort but not harm. However, the sudden shock could be alarming and catalyze other accidents.

High-Temperature Plasma - Do not operate this device near any flammable liquids or gases. The electric spark may ignite them.

Ozone Generator - Ozone, produced at the electrode tip, has a somewhat pungent odor but should dissipate harmlessly in a ventilated area. Do not use in confined spaces with poor ventilation.

High Frequency (RF) - If you wear a pacemaker or other medical electronic device, consult your physician before use.

Operating Procedures

Detailed Specifications

Reference Documentation

Operating Manual

From:

https://microfluidics.cnsi.ucsb.edu/wiki/ - Innovation Workshop Wiki

Permanent link:

https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=electro-technic_treater&rev=1675116509

Last update: 2023/01/30 22:08

