# Stratasys Objet30 Pro 3D Printer (Decommissioned)



**Tool Type:** 3D printer **Location:** Microfluidics Lab

**Description:** Polyjet 3D printer **Manufacturer:** Stratasys

#### **About**

The Objet 30 has been removed from the lab. Due to a high cost of maintenance and relatively low usage, we've decided to retire this tool. If you relied on this tool for "glossy" prints, please reach out to Brian Dincau, who has developed a method for achieving similarly glossy prints from Form3 resin prints.

The Objet30 Pro is a very accurate and versatile tool that can be utilized with different types of printing materials. The printer has two print heads – one prints the structural material for parts, and the other prints a support material. Parts are built on a layer of the support material. Matt finish parts are surrounded in support, and overhanging features are supported with support material during printing. The support material is removed in the water jet station. This is a great tool for accurate and precise models.

### **Safety Concerns**

#### **Printer Operation**

• The printer should only be operated by persons trained by Brian or any Workshop Wizard.

- Last update: 2024/07/23 18:32
  - Gloves should be worn when working with the print resins and when cleaning the print heads
  - All personnel operating or maintaining the printer should know the location of first aid and emergency equipment and how to use it.
  - Never block access to this equipment!
  - Keep fingers and other body parts clear of the printer cover when closing it.
  - Never attempt to open the main cover of the printer while it is working!
  - Never override the interlock safety switch!
  - If the interlock safety switches ever fail, do not use the printer.
  - Several parts of the printer remain extremely hot even after it has stopped operating. Avoid touching the UV lamp and the print block.

# **Training Documentation**

**Objet Training SOP** 

## **Post-Processing**

3D print water jet cleaning station

# **Detailed Specifications**

Model Materials	<b>Rigid Opaque:</b> VeroWhitePlus™, VeroBlackPlus™, VeroGray™, VeroBlue™ <b>Transparent:</b> VeroClear™Simulated <b>Polypropylene:</b> Rigur™ and Durus™ High Temperature
Support Material	SUP705 gel-like photopolymer support
Maximum Build Size (XYZ)	294 x 192 x 148.6 mm (11.57 x 7.55 x 5.85 in.)
System Size and Weight	82.6 x 60 x 62 cm (32.5 x 23.6 x 24.4 in.); 106 kg (234 lbs.)
Resolution	<b>X-axis:</b> 600 dpi; <b>Y-axis:</b> 600 dpi; <b>Z-axis:</b> 900 dpi
Accuracy	0.1 mm (0.0039 in.) varies depending on part geometry, size, orientation, material and post-processing method
Minimum Layer Thickness	28 microns (0.0011 in.); 16 microns for VeroClear material (.0006 in.)
Build Modes	<b>High quality:</b> 16-micron (.0006 in.) resolution <b>High speed:</b> 28-micron (.001 in.) resolution
Software	Objet Studio™ intuitive 3D printing software
OS Compatibility	Windows XP/Windows 7/Windows 8
Network Connectivity	Ethernet TCP/IP 10/100 base T
Operating Conditions	Temperature 18-25°C (64-77°F); relative humidity 30-70%
Power Requirements	<b>Single phase:</b> 100-120V; 50-60Hz; 7A or 200-240V; 50-60Hz 3.5A
Regulatory Compliance	CE, FCC/RoHS

#### **Reference Documentation**

- Cleaning Objet parts with Sodium Hydroxide
- Making 3D printed Molds
- Post Processing
- Users Guide

**Print Head Cleaning** 

Print Head Cleaning

Build Tray Cleaning 1

**Build Tray Cleaning 1** 

**Build Tray Cleaning 2** 

**Build Tray Cleaning 2** 

Build Tray Cleaning 3

**Build Tray Cleaning 3** 

Head Allignment

**Head Allignment** 

Load Cells Calibration

Load Cells Calibration

Pattern Test

Pattern Test

System Shutdown

systemshutdown.mp4

**UV** lamp Cleaning

**UV lamp Cleaning** 

Wiper Cleaning Inspection

Wiper Cleaning Inspection

From:

https://microfluidics.cnsi.ucsb.edu/wiki/ - Innovation Workshop Wiki

Permanent link:

https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=objet30pro

Last update: 2024/07/23 18:32

