

# Ultimaker S5 Dual FDM 3D Printer

Last updated: 5/31/23 Haley

Ultimaker S5

<b>Tool Type:</b> 3D printer
<b>Location:</b> Innovation Workshop
<b>Description:</b> Dual extrusion FDM 3D printer
<b>Manufacturer:</b> Ultimaker

---

## About

The Ultimaker S5 is a filament fed fusion deposition 3D printer capable of simultaneously printing two different plastics at once. Typically the printer is set up with ABS as a build material, and PVA as a solvable support material.

---

## Safety Concerns

- The print heads can be very hot - do not touch them with bare hands unless positive they are cool.
- As with any automated machinery make sure that your body is clear of the moving parts to avoid injury.

---

## Training Documentation

[FDM Training SOP](#)

## Detailed Specifications

Ultimaker S5:

- Build Volume: 330x240x300 mm
  - Filament diameter: 2.85 mm
  - XYZ resolution: 6.9, 6.9, 2.5 micron
  - Build plate temperature: 20-140 °C
  - Nozzle Temperature: 180-280 °C
- 

## Reference Documentation

PVA Temps:

Extruder: 220 C Bed: Whatever structural filament recommends

ABS Temps:

Extruder: 230 C Bed: 100 C

ultimaker s5 specs

Quick start guide

[um180129\\_ultimaker\\_3\\_manual\\_rb\\_v12\\_english.pdf](#)

<https://support.ultimaker.com/hc/en-us/articles/360012007119>

[pva\\_drying\\_recipe.pdf](#)

[ultimaker\\_filaments\\_-\\_sheet1.pdf](#)

[failed\\_3d\\_print\\_procedure.pdf](#)

---

From:

<https://microfluidics.cnsi.ucsb.edu/wiki/> - Innovation Workshop Wiki

Permanent link:

[https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=ultimaker3\\_extended&rev=1721779696](https://microfluidics.cnsi.ucsb.edu/wiki/doku.php?id=ultimaker3_extended&rev=1721779696)

Last update: **2024/07/24 00:08**

