

Material Safety Data Sheet

EpoxAcast ® 670 HT

Date Of Preparation: March 8, 2011 Revision: 0001

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: EpoxAcast ® 670 HT

General Use: Epoxy Tooling

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924 International 813-248-0585

Section 2- Hazards Identification

Not hazardous according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Council directive 1999/45/EC and its subsequent amendments.



MSDS No. 418

Section 3 - Composition / Information on Ingredients

No hazardous ingredients

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention. **Skin Contact:** In case of skin contact, wash thoroughly with soap and water; remove

contaminated clothing and launder before reuse.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician

immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >280 °F (138 °C) Flash Point Method: PMCC

Flammability Classification: Non-Flammable

Extinguishing Media: Foam, Dry Chemical, and Carbon Dioxide

Unusual Fire or Explosion Hazards: None

Hazardous Combustion Products: Oxides of Nitrogen and Carbon, Acids

and Aldehydes when burned.

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

NFPA

Revision: 0001

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike and contain spill; absorb or scrape up excess into suitable

container for disposal. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eyeand face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.





Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Water Solubility: negligible

Appearance and Odor: Off-white viscous liquid, mild odor

Boiling Point: None (Polymeric Resin)
Freezing/Melting Point: None (Polymeric

Vapor Pressure: None (Polymeric Resin)

Resin)

Vapor Density (Air=1): None (Polymeric Evaporation Rate: None (Polymeric

Resin) Resin)

Specific Gravity (H₂O=1, at 4 °C): 1.4 Viscosity: 200 poise

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizing agents, strong Lewis or mineral acids.

Conditions to Avoid: Mixing with Amines under uncontrolled conditions.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce: Oxides of

Nitrogen and Carbon, Acids and Aldehydes when burned.

Section 11- Toxicological Information

Eye Effects: Irritation
Skin Effects: Irritation

Carcinogenicity: None Determined
Mutagenicity: None Determined
Teratogenicity: None Determined

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: Must be disposed of in accordance with applicable Federal, state and local regulations.

Section 14 - Transport Information

DOT IATA IMDG

Not Regulated Not Regulated Not Regulated

Section 15 - Regulatory Information

United States Regulations

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

SARA Toxic Chemical (40 CFR 372.65): None

This product does not contain chemicals that are subject to release reporting requirements under section 313 of SARA Title III.

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

<u>California Proposition 65</u>: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

CANADA Regulations

WHMIS Identification: Not controlled

CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): All are Listed

Labeling according to EEC Directive

No special packaging or labeling requirements.

Revision: 0001

Revision: 0001

Section 16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA)Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



Material Safety Data Sheet

EpoxAcast ® 670 HT

Revision: 0001

MSDS No. 418

Date Of Preparation: March 8, 2011

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: HT Hardener Other Designations: Curing Agent, Epoxy

General Use: Laminating, Adhesive and Casting Resin

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924 International 813-248-0585

Section 2- Hazards Identification

Hazard Designation:















Xn: Harmful C: Corrosive N: Dangerous for the environment

Risk Phrases pertaining to particular dangers

R21/22: Harmful in contact with skin and if swallowed.

R34: Causes burns. R36: Irritating to eyes.

R43: May cause skin sensitization by contact.

R48/22: Harmful: danger of serious damage to health by prolonged exposure if swallowed. **R50/53:** Very toxic to aquatic organisms may cause long term adverse effects in the aquatic

environment.

Classified according to Articles 6 & of Directive 1999/45/EC

Section 3 - Hazards Identification

Component	ACGIH TWA	Exposure Limits OSHA PEL	Hazard Designation	Weight Percent (%)
Diethyltoluenediamine CAS Number: 68479-98-1 EINECS Number: 270-877-4	None Established	None Established	Xn N	80-90
Diethylenetriamine CAS Number: 111-40-0 EINECS Number: 203-865-4	1 PPM	1 PPM	C	10-20

Section 4 - First Aid Measures

Inhalation: Remove too fresh air; if breathing is labored seek medical attention.

Eye Contact: Flush with water for 15 minutes; seek medical attention

Skin Contact: remove with soap and water: if redness or rash develops seek medical attention:

Launder contaminated clothing before reuse.

Ingestion: do not induce vomiting; seek medical attention

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >200 °F (93 °C)

Flammability Classification: Combustible Liquid, Class III Extinguishing Media: Foam, Dry Chemical, and Carbon Dioxide

Unusual Fire or Explosion Hazards: None

Hazardous Combustion Products: May generate Ammonia gas,

Oxides of Nitrogen and Carbon when burned

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.



Revision: 0001

Section 6 - Accidental Release Measures

Spill /Leak Procedures

Containment: Dike and contain for later disposal. Do not release into sewers or waterways. **Cleanup:** Cover minor spills with sodium bisulfate to neutralize and reduce vapors. Spray with water. Place in metal containers for recovery or disposal. Clean-up personnel must be equipped with self-contained breathing apparatus and butyl rubber protective clothing. **Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Avoid prolonged or repeated eye and skin contact. Avoid breathing vapors and use only with adequate ventilation. Use good general housekeeping procedures. **Storage Requirements:** Keep away from oxidizers. Store in Closed containers. Use only with adequate ventilation.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas

Protective Clothing/Equipment: Wear chemically protective gloves, boots, and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.











Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance: Amber to reddish brown

liquid

Odor: Ammonia odor

Vapor Pressure: None Determined

Vapor Density (Air=1): >1

Specific Gravity (H2O=1, at 4 °C): 0.984

Water Solubility: Negligible: Boiling Point: 390 °F(199 °C) % Volatile: None Determined

Freezing/Melting Point: None Determined

Revision: 0001

Evaporation Rate: None Determined)

Section 10 - Stability and Reactivity

Stability: This material is stable at room temperature in closed containers under normal storage

and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizing agents, strong Lewis or mineral acids.

Conditions to Avoid: Mixing with epoxies under uncontrolled conditions.

Hazardous Decomposition Products: Thermal oxidative decomposition of can produce: Ammonia gas, Oxides of Nitrogen and Carbon when burned. Combustion of product under oxygen-starved conditions can be expected to produce numerous toxic products including nitriles, cyanic acid, isocyanates, cyanogens, nitrosamines, amides, and carbamates.

Section 11- Toxicological Information

Eye Effects: will cause burns

Mutagenicity: No Data

Skin Effects: will cause burns

Teratogenicity: No Data

Acute Toxicity Effects Data: No Data

Section 12 - Ecological Information

Not Determined

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT IATA IMDG
Shipping Name: Shipping Name: Shipping Name:
Diethylenetriamine Diethylenetriamine Diethylenetriamine

UN #: 2079 **UN #:** 2079 **UN #:** 2079

Hazard Class: 8
Packing Group II
Label: Corrosive

Hazard Class: 8
Packing Group II
Label: Corrosive

Hazard Class: 8
Packing Group II
Label: Corrosive

Label: Corrosive

Revision: 0001

Section 15 - Regulatory Information

SARA 312 (40 CFR #70) Hazard Classification: Acute Health Hazard, Chronic Health Hazard

TSCA Inventory Status (40CFR710): All components of this formula are on the TSCA inventory

<u>California Proposition 65</u>: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

CANADIAN REGULATIONS:

WHMIS Identification: Class D-1B: Material causing immediate and serious toxic effects (Toxic). CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **Listed on DSL**



Labeling according to EEC Directive

Risk Phrases	Symbol(s) Required for EU Label	Safety Phrases	
R21/22: Harmful in contact		S1/2: Keep locked up and	
with skin and if swallowed.		out of reach of children	
R34: Causes burns.		S26: In case of contact with	
R36: Irritating to eyes.	Xn: Harmful	eyes, rinse immediately with	
R43: May cause skin	2000 2000 200	plenty of water and seek	
sensitization by contact.	.=	medical advice	
R48/22: Harmful: danger of		S36/37/39: Wear suitable	
serious damage to health by		protective clothing, gloves,	
prolonged exposure if	C: Corrosive	and eye face/protection. S45: In case of an accident or if you feel sick, seek	
swallowed.	N		
R50/53: Very toxic to aquatic			
organisms may cause long		medical attention.	
term adverse effects in the	N. D	S60: The material and its	
aquatic environment.	N: Dangerous for the environment	container must be disposed	
		as a hazardous waste.	
		S61: Avoid release to the	
		environment.	

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA)Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.